

MATERIAL SAFETY DATA SHEET



SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER/SUPPLIER NAME: Clariant Corporation, AZ Electronic Materials

PO Box 3700, 70 Meister Avenue Somerville, NJ 08876-1258

Emergency-CHEMTREC: (800) 424-9300 **TELEPHONE NUMBERS:**

Product Safety Information: (908) 429-3593

Customer Service: (800) 515-4164

AZ(R) 327 MIF DEVELOPER PRODUCT NAME:

None SYNONYMS:

7035 MSDS NO.

11/23/1999 **REVISION DATE:** 12/13/2000 DATE PRINTED:

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name & CAS Number	Weight Percent	<u>Hazardous?</u>	NJ Trade Secret#	Ingredient Synonyms	Other Information:
Tetramethylammonium hydroxide	2	Yes	No	TMAH	None
000075-59-2 Ammonium lauryl sulfate 002235-54-3	1	Yes	67829000004-5759P	None	Trade secret per NJ/PA RTK laws.

Chemical Name & CAS Number	Weight Percent	Hazardous?	NJ Trade Secret #	Ingredient Synonyms	Other Information:
Water 007732-18-5	>95	No	NA	None	NJ/PA RTK listings. Not on any other state RTK list.

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Clear liquid with slight amine odor. Noncombustible, Water soluble, Causes moderate skin irritation. Causes moderate eye irritation. Toxic by skin absorption. EMERGENCY OVERVIEW:

POTENTIAL HEALTH EFFECTS:

Clariant Corporation, AZ Electronic Materials AZ(R) 327 MIF DEVELOPER 7035 11/23/1999

REVISION DATE:

Eye:

Causes moderate eye irritation.

Skin:

Causes moderate skin irritation. Toxic by skin absorption.

Ingestion:

May be harmful if swallowed.

Inhalation:

No hazard in normal industrial use.

Systemic Effects:

No hazard in normal industrial use.

Reproductive & birth defects:

No information.

Relevant Routes of Exposure:

Liquid and mist contact with skin and eyes. Inhalation of mist.

Medical Conditions Aggravated:

Preexisting skin and eye conditions may be aggravated.

ENVIRONMENTAL OVERVIEW:

Toxic or highly toxic to fish and daphnids. Resistant to biodegradation.

SECTION 4. FIRST AID MEASURES

FIRST AID PROCEDURES:

Inhalation:

Remove victim to fresh air. Consult physician if irritation occurs.

Eye Contact:

Flush thoroughly with water for 15 minutes. Get immediate medical help.

Skin Contact:

Immediately remove contaminated clothing and wash affected area thoroughly with soap and water. Consult physician if exposure is extensive or if irritation occurs.

Ingestion:

If person is conscious, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Do not induce vomiting. Consult physician.

NOTE TO PHYSICIANS:

A component of this material causes severe acute toxicity in experimental animals by the oral or dermal route of exposure. Exposed individuals should be cafefully observed and treated according to symptoms.

SECTION 5. FIRE FIGHTING MEASURES

Noncombustible. Water-based material with low organic content. Compatible with extinguishing agents.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:

Wearing appropriate personal protective equipment, contain spill, collect onto inert absorbent, and place in a suitable container. Rinse residual with water.

Clariant Corporation, AZ Electronic Materials AZ(R) 327 MIF DEVELOPER 7035 REVISION DATE: 11/23/1999

SECTION 7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.

Storage:

Store in original container. Store at appropriate temperature. See label for details. Keep from freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Where mist is present, provide local exhaust ventilation or a respirator certified for mist by NIOSH.

Personal Protective Equipment (PPE):

Clothing suitable to prevent skin contact. Safety eyewear to protect against splashes. Rubber gloves.

Exposure Guidelines:

Chemical Name & CAS Number	Weight Percent	Manufacturer's TWA TLV'	ACGIH TWA TLV*	OSHA PEL*	NIOSH REL*	AIHA WEEL*
Tetramethylammonium hydroxide 000075-59-2	2					
Ammonium lauryl sulfate 002235-54-3	1					

Chemical Name & CAS Number	Weight Percent	Manufacturer's TWA TLV*	ACGIH TWA TLV*	OSHA PEL*	NIOSH REL*	AIHA WEEL*
Water 007732-18-5	>95					

^{*}TWA TLV = Time Weighted Average Threshold Limit Value

ACGIH = American Conference of Governmental Industrial Hygienists

OSHA PEL = Occupational Safety and Health Administration Permissable Exposure Limit

NIOSH REL = National Institute of Occupational Safety and Health Recommended Exposure Limit

AIHA WEEL = American Industrial Hygiene Association Workplace Environmental Exposure Level

**Skin Notation

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, coforless liquid.

Odor: Slight amine odor.

Physical State: Liquid with dissolved solids.

pH 13.4

Vapor Pressure aprox the same as water

Boiling Point: 100 deg C. Solubility in water: Soluble.

^{***}Hoechst Celanese Workplace Exposure Level (HCC WEL); included is a "no contact" recommendation for NMP due to its skin absorption properties.

Clariant Corporation, AZ Electronic Materials AZ(R) 327 MIF DEVELOPER 7035 REVISION DATE: 11/23/1999

Specific gravity:

1.0

Evaporation rate

(butyl acetate=1):

approx same as water

% Volatile:

97

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability:

Stable.

Hazardous Polymerization:

Will not occur.

Conditions to Avoid:

Avoid contact with strong acids. This product is expected, by test or analogy, to slowly attack aluminum and perhaps other nonferrous metals, releasing hydrogen gas.

Hazardous Decomposition Products:

If heated to dryness, TMAH may decompose to trimethylamine and methanol. TMAH reportedly decomposes in boiling water, rate unknown.

SECTION 11. TOXICOLOGICAL INFORMATION

Carcinogen:

IARC: NO NTP: NO OSHA: NO

Ingredient Toxicity Data:

Chemical Name & CAS Number	Weight Percent	oral rat LD50	skin rbt LD50	inh rat LC50
Tetramethylammonium hydroxide 000075-59-2	2	50 mg/kg as TMAH chloride salf	25 mg/kg (g pig)	
Ammonium lauryl sulfate 002235-54-3	1			

Chemical Name & CAS Number	Weight Percent	oral rat LD50	skin rbt LD50	inh rat LC50
Water 007732-18-5	>95			

TOXICITY HAZARD STATEMENTS FOR PRODUCT:

Eve Effects:

Testing in rabbits shows that the material is a moderate eye irritant.

Skin Effects:

Testing in animals shows that this material is a moderate skin irritant. D.O.T. four hour rabbit skin test of the highest commercial concentration of this product was negative for skin corrosion. Based on animal testing, the acute toxicity of this material via the dermal route is classified as toxic (rabbit or rat dermal LD50 between 200 and 1000 mg/kg)

Clariant Corporation, AZ Electronic Materials AZ(R) 327 MIF DEVELOPER 7035 11/23/1999

REVISION DATE:

Acute Oral Effects:

Testing in animals shows that this material is harmful (rat acute oral LD50 between 500 and 5000 mg/kg).

Subchronic Effects:

No information available.

Chronic Effects:

No information available.

Mutagenicity/Genotoxicity:

No information

SECTION 12. ECOLOGICAL INFORMATION

Ingredient Ecological Toxicity Data:

Chemical Name & CAS Number	Weight Percent	Fish LC50	Daphnia EC50	Algae IC50
Tetramethylammonium hydroxide 000075-59-2	2	35.1 mg/l (as chloride)	0.21 mg/l (as chloride)	
Ammonium lauryl sulfate 002235-54-3	1			

Chemical Name & CAS Number	Weight Percent	Fish LC50	Daphnia EC50	Algae IC50
Water 007732-18-5	>95			

Environmental hazard information statements (using EU classification criteria):

Toxicity to fish:

Harmful (LC50 between 10 and 100 mg/L).

Toxicity to daphnids:

Very Toxic (EC50 less than 1 mg/L).

Environmental Fate:

Testing indicates that this material is resistant to biodegradation; however, it should be effectively removed under the conditions encountered in a typical water treatment plant.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal:

Consult local, state, and federal regulations. This product would be considered a hazardous waste under RCRA due to high pH unless neutralized prior to disposal.

SECTION 14. TRANSPORT INFORMATION

Clariant Corporation, AZ Electronic Materials AZ(R) 327 MIF DEVELOPER 7035 11/23/1999 REVISION DATE:

DOT/IATA Shipper Entry:

Caustic alkali liquid, n.o.s. (tetramethylammonium hydroxide), 8, UN1719, III.

Other Information:

Classification due to corrosivity of aluminum.

SECTION 15. REGULATORY INFORMATION

TSCA Inventory Status:

All components of this product are listed on the TSCA Inventory.

SARA Title III section 313:

This product is not subject to SARA Title III Section 313 reporting requirements under 40CFR372.

OSHA Physical Hazards:

None

OSHA Health Hazards:

Eye Hazard, Irritant, Skin Hazard, Toxic. SARA (311, 312) Hazard Class(es):

Acute health hazard.

SECTION 16. OTHER INFORMATION

HMIS Ratings:

Health = 2; Flammability = 0; Reactivity = 0; PPE=X

NFPA Ratings:

Health = 2: Flammability = 0; Reactivity = 0; Special Hazard = None.

Special Precautions:

The tetramethylammonium ion (TMA), as TMAH, in this developer is toxic at low levels to the water flea ceriodaphnia dubia (CD) used in the whole effluent toxicity (WET) biomonitoring test. Data from the supplier suggests that continuous input of 60-100 ppm TMA to a small POTW should not cause WET toxicity. It is expected that discharges to a sizable POTW will not affect the ability to pass the WET tests. However, discharges to a small POTW or direct discharges to surface waters should be carefully reviewed. Contact AZ Electronic Materials Product Safety for additional information (908-429-3593 or 908-429-3562).

(R) and TM indicate trademarks of Clariant AG, its business partners or suppliers. The information herein is provided in good faith, but no warranty, express or implied, is made with respect to such information.